AFRICA TWIN DCT



ENGINE
Type: 4-stroke, Unicam®
Displacement: 1,084 cc, parallel twin-cylinder, 4 valves per cylinder
Cooling: liquid
Maximum power: 101 hp @ 7,500 rpm
Torque: 112 Nm @ 5,500 rpm

FUEL SYSTEM
Type: PGM-FI programmed fuel injection
Fuel tank capacity: 18.8 liters

TRANSMISSION
Type: 6-speed DCT (Dual Clutch Transmission)
Final drive: chain

DIMENSIONS
Overall dimensions (L x W x H): 2,930 mm x 960 mm x 1,485 mm
Wheelbase: 1,575 mm
Seat height: 850 / 870 mm
Ground clearance: 250 mm
Curb weight: 242 kg

BRAKES
Front: dual 310 mm discs, radial-mount 4-piston Nissin® hydraulic calipers, IMU-synchronized ABS
Rear: 256 mm lobed disc, 1-piston Nissin® hydraulic caliper, IMU-synchronized ABS (switchable)

TIRES
Front tire: 90/90-21M/C
Rear tire: 150/70-R18M/C

SUSPENSION
Front: Showa® inverted fork, 45 mm diameter, with preload, compression, and rebound damping adjustment, 230 mm travel
Rear: cast aluminum Pro-Link® swingarm with Showa® gas shock, hydraulic preload and rebound adjustment, 220 mm travel

INSTRUMENTS & IGNITION
Ignition type: digital transistorized
Instrument panel: 6.5-inch LCD Touch
Connectivity: bluetooth Audio and Apple CarPlay
Main headlight: LED

SPECIAL FEATURES
- HSTC torque control with anti-wheelie and coordinated braking, managed by a 6-axis Inertial Measurement Unit (IMU)
- 4 riding modes + 2 customizable modes.
- Throttle by wire
- USB 1.5A and 12V connectors
- Engine skid plate

8752-8715 HONDAMOTOS.CR MOTOSHONDACR

HONDA